

# LAN Phone 399

## Multi-Lines IP Phone Solution

NEW

### Application

- ISP/ITSP (Internet Telephony Service Provider)
- IP-PBX with office telephony services
- Multi-nation enterprise communication
- SOHO Telephony

### Calling Features

- Call Hold
- Call Transfer
- Call Forward
- Call Waiting
- Call Conference
- DND (Do Not Disturb)
- Call List (Missed,Received,Dialed)
- 2 configurable speed dials
- Support up to 3 multi-lines

### Network Support

- Fixed IP
- Dynamic Host Configuration Protocol (DHCP)
- PPPoE connection
- Support QOS by setting DSCP (Differentiated Service Code Point) parameters of VoIP packet
- Support NAT function
- Support STUN Function

### Technical Specification

- Two 10/100 Base-T Ethernet ports with Switch or NAT inside
- LCD Configuration Password Protection
- 2x16 character LCD display
- LCD Display Time, Date, Caller ID, Call Duration

### Audio Features

- G.711 A/μ-Law, G.729, G.726
- Provide In-band and Out-band DTMF generation/detection

### Provisioning and Configuration

- SIP (RFC3261) compliance
- LCD configuration password protection
- Provide adjustable Ringer , Speaker and Handset volume
- Support DNS server inquiry

### Management Features

- Software Upgrade: TFTP download
- Easy ways for system configuration
  - A. LCD Front Panel
  - B. Web Browser
  - C. TELNET
  - D. Provision Server

### Certification

- CE, FCC

### Power Supply

- DC12V output adaptor, AC 100-240Vac input

### Operation Environment

- Humidity: 10 to 90 % (Non-condensing)
- Operational Temperature: 0 to +40°C

### Storage Environment

- Humidity: 10 to 90 % (Non-condensing)
- Storage Temperature: -10 to +50°C

